

POWER/MECHANICALLY OPERATED GUILLOTINES (MAG)



Models Available:
 3200mm x 3.2mm (MAG3050)
 2500mm x 3.2mm (MAG2500)
 2000mm x 3.2mm (MAG2000)
 1250mm x 3.5mm (MAG1250)

- CE Certified
- 1000mm Squaring Arm with Rule & Flip up Sides.
- 1000mm Front Support Arms
- 800mm Working Table Height
- Electric Foot Control
- E21s Controller - Features "Go To" positioning, Programmable Steps, Stock Counter, One Side Positioning & Retract Facility.
- Side Fences & Top Fence with Opto-Electrical Guards.
- Cutting Illumination.
- Hand Moveable Foot Pedal Control including Emergency Stop.
- Bed Infill Plates with Ball Transfers.
- 400v, 3 Phase Electrics, 50Hz
- 32AMP 3-phase, Type-D Breaker Required

These Power/Mechanically Operated Guillotines (MAG) are lightweight, robust machines designed for precision and durability - achieving superior, precise cuts with minimal effort.. Available in 4 size options, these machines are equipped to meet a range of cutting needs. Each model comes with a 1000 mm squaring arm featuring a rule and flip-up stops and front 1000 mm support arms to facilitate ease of operation. The E21S Control System enhances operational efficiency with features like "Go To" positioning, programmable steps, a stock counter, one-side positioning, and a retract facility for increased productivity. These machines operate on a 400V/3PH/50Hz electrical setup and come standard with optoelectrical rear guards and an electric footswitch.

Designed for demanding environments, these mechanical guillotines are built to withstand heavy-duty use, making them ideal for industrial applications. Engineered with durable components, they deliver consistent performance and long-lasting reliability, even under continuous operation.

Constructed with high-quality materials, these machines offer exceptional stability and strength. The solid build minimises vibrations and ensures precise cutting every time, allowing you to handle a wide range of materials with confidence.

SPECIFICATIONS

Model:	Cutting Length:	Maximum Thickness:	Back Guard:	Cutting Angle:	Strokes:	Motor Power:	Supply Voltage:	Length:	Width:	Height:
MAG3050	3200mm	3.2mm	Up to 650mm	1°30	47/Min	11kW	400v, 3 Phase Electrics, 50Hz	3630mm	2250mm	1400mm
MAG2500	2500mm	3.2mm		1°18		7.5kW		3124mm	2210mm	1180mm
MAG2000	2000mm	3.2mm		1°45		7.5kW		2624mm	2210mm	1180mm
MAG1250	1250mm	3.5mm		1°30		5.5kW		1860mm	2210mm	1180mm