

WNS Hand Swager (HS215)

Manufactured by W. NEAL SERVICES LTD

W. NEAL SERVICES LTD
 29 Purdeys Way
 Purdeys Industrial Estate
 Rochford
 Essex
 SS4 1ND
 ENGLAND



WNS Hand Swager
 215mm (8.5") Throat x
 1.2mm Capacity.
 (HS215)



Optional Stand (shown) available separately

WNS HAND SWAGERS (HS215) are principally used for swaging, beading, wiring, crimping and forming of sheet metal. The HS215 has a 215mm (8.5") Throat and can accommodate mild steel sheet up to 1.2mm thick. This machine comes complete with 6 sets of rolls.

SPECIFICATIONS

Model:	Throat:	Maximum Thickness:	Number of Rolls (x 6):	Length:	Width:	Height:	Weights - net/gross:
HS215	215mm (8.5")	1.2mm <i>(Subject to rolls)</i>	6 Sets	600mm	250mm	500mm	33Kg/53Kg

Revised: Mar 2020

All capacities are based on the use of Rollforming quality Mild Steel unless otherwise stated. All specifications, dimensions & weights are approximate & are to be used as a guide. Colours may vary. Please note photographs/drawings are not to scale. All prices are subject to delivery costs and applicable VAT. W. Neal Services Ltd reserves the right to alter any specifications. *For warranty terms please see our full [Terms & Conditions](#). E&OE.

WNS Swager Rolls

Manufactured by W. NEAL SERVICES LTD

W. NEAL SERVICES LTD
 29 Purdeys Way
 Purdeys Industrial Estate
 Rochford
 Essex
 SS4 1ND
 ENGLAND

*Indicates Standard Rolls

SPECIFICATIONS

SWAGING ROLLS*			JENNY/FLANGING ROLLS*																					
	<table border="1"> <thead> <tr> <th>WNS Power Swager (PS280)</th> <th>WNS Power/Hand Swager (PS215/HS215)</th> </tr> </thead> <tbody> <tr> <td>Diameter (D):</td> <td>Diameter (D):</td> </tr> <tr> <td>S1</td> <td>3.0mm</td> </tr> <tr> <td>S2</td> <td>5.0mm</td> </tr> <tr> <td>S3</td> <td>6.0mm</td> </tr> <tr> <td>S4</td> <td>8.0mm</td> </tr> <tr> <td>S5</td> <td>10mm</td> </tr> <tr> <td>S6</td> <td>12mm</td> </tr> </tbody> </table>	WNS Power Swager (PS280)	WNS Power/Hand Swager (PS215/HS215)	Diameter (D):	Diameter (D):	S1	3.0mm	S2	5.0mm	S3	6.0mm	S4	8.0mm	S5	10mm	S6	12mm	<table border="1"> <thead> <tr> <th>WNS Power Swager (PS280)</th> <th>WNS Power/Hand Swager (PS215/HS215)</th> </tr> </thead> <tbody> <tr> <td>Step:</td> <td>Step:</td> </tr> <tr> <td>3.0mm</td> <td>3.0mm</td> </tr> </tbody> </table>	WNS Power Swager (PS280)	WNS Power/Hand Swager (PS215/HS215)	Step:	Step:	3.0mm	3.0mm
	WNS Power Swager (PS280)	WNS Power/Hand Swager (PS215/HS215)																						
	Diameter (D):	Diameter (D):																						
	S1	3.0mm																						
	S2	5.0mm																						
	S3	6.0mm																						
	S4	8.0mm																						
S5	10mm																							
S6	12mm																							
WNS Power Swager (PS280)	WNS Power/Hand Swager (PS215/HS215)																							
Step:	Step:																							
3.0mm	3.0mm																							

WIRING ROLLS*			NECKING ROLLS*																					
	<table border="1"> <thead> <tr> <th>WNS Power Swager (PS280)</th> <th>WNS Power/Hand Swager (PS215/HS215)</th> </tr> </thead> <tbody> <tr> <td>Diameter (D):</td> <td>Diameter (D):</td> </tr> <tr> <td>W1</td> <td>3.0mm</td> </tr> <tr> <td>W2</td> <td>5.0mm</td> </tr> <tr> <td>W3</td> <td>6.0mm</td> </tr> <tr> <td>W4</td> <td>8.0mm</td> </tr> <tr> <td>W5</td> <td>10mm</td> </tr> <tr> <td>W6</td> <td>12mm</td> </tr> </tbody> </table>	WNS Power Swager (PS280)	WNS Power/Hand Swager (PS215/HS215)	Diameter (D):	Diameter (D):	W1	3.0mm	W2	5.0mm	W3	6.0mm	W4	8.0mm	W5	10mm	W6	12mm	<table border="1"> <thead> <tr> <th>WNS Power Swager (PS280)</th> <th>WNS Power/Hand Swager (PS215/HS215)</th> </tr> </thead> <tbody> <tr> <td>Step:</td> <td>Step:</td> </tr> <tr> <td>4.0mm</td> <td>3.5mm</td> </tr> </tbody> </table>	WNS Power Swager (PS280)	WNS Power/Hand Swager (PS215/HS215)	Step:	Step:	4.0mm	3.5mm
	WNS Power Swager (PS280)	WNS Power/Hand Swager (PS215/HS215)																						
	Diameter (D):	Diameter (D):																						
	W1	3.0mm																						
	W2	5.0mm																						
	W3	6.0mm																						
	W4	8.0mm																						
W5	10mm																							
W6	12mm																							
WNS Power Swager (PS280)	WNS Power/Hand Swager (PS215/HS215)																							
Step:	Step:																							
4.0mm	3.5mm																							

CRIMPING ROLLS		SCREW IN ROLLS Maximum Thickness: 0.8mm		FLAT/PLAIN ROLLS*																
	<table border="1"> <thead> <tr> <th>WNS Power Swager (PS280)</th> </tr> </thead> <tbody> <tr> <td>Width:</td> </tr> <tr> <td>38mm</td> </tr> </tbody> </table>	WNS Power Swager (PS280)	Width:	38mm		<table border="1"> <thead> <tr> <th>WNS Power Swager (PS280)</th> </tr> </thead> <tbody> <tr> <td>Diameter (D):</td> <td>Flange Height:</td> </tr> <tr> <td>6.0mm</td> <td>7.0mm</td> </tr> </tbody> </table>	WNS Power Swager (PS280)	Diameter (D):	Flange Height:	6.0mm	7.0mm		<table border="1"> <thead> <tr> <th>WNS Power Swager (PS280)</th> </tr> </thead> <tbody> <tr> <td>Roll Diameter:</td> <td>Width:</td> </tr> <tr> <td>PW1</td> <td>81mm</td> <td>25mm</td> </tr> </tbody> </table>		WNS Power Swager (PS280)	Roll Diameter:	Width:	PW1	81mm	25mm
	WNS Power Swager (PS280)																			
Width:																				
38mm																				
WNS Power Swager (PS280)																				
Diameter (D):	Flange Height:																			
6.0mm	7.0mm																			
WNS Power Swager (PS280)																				
Roll Diameter:	Width:																			
PW1	81mm	25mm																		
<table border="1"> <thead> <tr> <th>WNS Power/Hand Swager (PS215/HS215)</th> </tr> </thead> <tbody> <tr> <td>Width:</td> </tr> <tr> <td>20mm</td> </tr> </tbody> </table>	WNS Power/Hand Swager (PS215/HS215)	Width:	20mm	<table border="1"> <thead> <tr> <th>WNS Power/Hand Swager (PS215/HS215)</th> </tr> </thead> <tbody> <tr> <td>Diameter (D):</td> <td>Flange Height:</td> </tr> <tr> <td>6.0mm</td> <td>6.0mm</td> </tr> </tbody> </table>	WNS Power/Hand Swager (PS215/HS215)	Diameter (D):	Flange Height:	6.0mm	6.0mm	<table border="1"> <thead> <tr> <th>WNS Power/Hand Swager (PS215/HS215)</th> </tr> </thead> <tbody> <tr> <td>Roll Diameter:</td> <td>Width:</td> </tr> <tr> <td>PW2</td> <td>53mm</td> <td>20mm</td> </tr> </tbody> </table>		WNS Power/Hand Swager (PS215/HS215)	Roll Diameter:	Width:	PW2	53mm	20mm			
WNS Power/Hand Swager (PS215/HS215)																				
Width:																				
20mm																				
WNS Power/Hand Swager (PS215/HS215)																				
Diameter (D):	Flange Height:																			
6.0mm	6.0mm																			
WNS Power/Hand Swager (PS215/HS215)																				
Roll Diameter:	Width:																			
PW2	53mm	20mm																		

NOMINAL OUTSIDE DIAMETER & SHAFT SIZE: PS280: 85mm & 30mm | PS215: 57mm & 20mm.
 Other rolls, such as Closing, V-Shaped, Knurled and odd diameters (for smaller tubes) available upon request.

Revised: Mar 2020

All capacities are based on the use of Rollforming quality Mild Steel unless otherwise stated. All specifications, dimensions & weights are approximate & are to be used as a guide. Colours may vary. Please note photographs/drawings are not to scale. All prices are subject to delivery costs and applicable VAT. W. Neal Services Ltd reserves the right to alter any specifications. *For warranty terms please see our full [Terms & Conditions](#). E&OE.