

WNS Punch and Flare Die Set (PFD-SET-13)



- 1.5mm Capacity Mild Steel
- Finish Hole Diameter +1/2"
 - Flare Height 1/4"
- Manufactured with Carbon Steel
 - Strengthens Panels
 - c/w 13 Dies
 - c/w Screw to Tighten
 - c/w Metal Case
- Sizes Included Range From 1/2" to 3"

WNS Punch and Flare Dies (PFD-SET-13) can create a smooth hole, with or without a flare in one easy step. Simply drill a pilot hole for the draw bolt, position the tool on the pilot hole, and tighten the bolt. Commonly used in automotive fabrication, providing both strength and aesthetical appeal. The following sizes are included in this set: 1/2", 5/8", 3/4", 1", 1 1/4", 1 1/2", 1 5/8", 1 3/4", 2", 2 1/4", 2 1/2", 2 3/4" and 3".

SPECIFICATIONS

Model:	Maximum Thickness:	Finish Hole Diameter:	Flare Height:			Packing Size: (L x H x W)			Weight - net/gross:		
PFD-SET-13	1.5mm Capacity Mild Steel	+1/2"	1/4"			300mm x 300mm x 80mm			18.5/19.5kg		
Die Details:	Inside Diameter/Hole Size:		1/2"	5/8"	3/4"	1"	1 1/4"	1 1/2"	1 5/8"	1 3/4"	2"
	Outside Diameter of the Die:		1"	1 1/8"	1 1/4"	1 1/2"	1 3/4"	2"	2 1/8"	2 1/4"	2 1/2"
	Inside Diameter/Hole Size:		2 1/4"	2 1/2"	2 3/4"	3"					
	Outside Diameter of the Die:		2 3/4"	3"	3 1/4"	3 1/2"					

All specifications, dimensions and weights are approximate and are to be used as a guide. Colours may vary. Please note photo graphs/drawings are not to scale. W. Neal Services Ltd reserves the right to alter any specifications. For warranty terms please see our full [Terms & Conditions](#). E&OE. (SEPT-25)